

// FRACKING

// 601AA

**Oil rigger-frac S&D 10 bar (150 psi)****Tube:** black NBR/PVC.**Reinforcement:** high tensile textile cords with embedded steel helix wire.**Cover:** black SBR - abrasion and ozone resistant.**Application:** crude oil mud handling in oilfield vacuum tank service.

Extensively used in fracking operations.

Temperature: -30 °C +80 °C (-22 °F +176 °F)

ID (mm)	ID (in)	OD (mm)	OD (in)	WP (bar)	WP (psi)	BP (bar)	BP (psi)	BR (mm)	BR (in)	Vacuum %	Weight (kg/m)	Weight (lb/ft)
51,0	2"	62,0	2,44	10	150	30	450	255	10,04	100,00	1,420	0,96
76,0	3"	89,0	3,50	10	150	30	450	380	14,96	90,00	2,630	1,77
102,0	4"	116,0	4,57	10	150	30	450	510	20,08	90,00	4,080	2,75
152,0	6"	168,0	6,61	10	150	25	375	760	29,92	80,00	7,010	4,72

// 6C1AA

**Oil rigger-frac Vacuum 10 bar (150 psi) - Corrugated****Tube:** black NBR/PVC.**Reinforcement:** high tensile textile cords with embedded steel helix wire.**Cover:** black SBR - abrasion and ozone resistant.**Application:** oilfield vacuum tank service for crude oil mud handling.

Light weight and flexible construction

Temperature: -30 °C +80 °C (-22 °F +176 °F)

ID (mm)	ID (in)	WP (bar)	WP (psi)	BP (bar)	BP (psi)	BR (mm)	BR (in)	Vacuum %	Weight (kg/m)	Weight (lb/ft)
51,0	2"	10	150	30	450	153	6,02	100,00	1,300	0,88
76,0	3"	10	150	30	450	223	8,78	90,00	2,400	1,62
102,0	4"	10	150	30	450	306	12,05	90,00	3,560	2,40
152,0	6"	10	150	30	450	608	23,94	90,00	6,700	4,51
203,0	8"	10	150	30	450	812	31,97	90,00	13,160	8,85

// 6D1AA

**Frac delivery 27 bar (400 psi)****Tube:** black synthetic elastomer.**Reinforcement:** high tensile textile cords.**Cover:** black synthetic elastomer - abrasion and ozone resistant.**Application:** fracking fluids, liquid mud and crude oil delivery in heavy duty oilfield and gas exploration service.**Temperature:** -30°C +80°C (-22°F +176°F)

ID (mm)	ID (in)	OD (mm)	OD (in)	WP (bar)	WP (psi)	BP (bar)	BP (psi)	Weight (kg/m)	Weight (lb/ft)
102,0	4"	120,0	4,72	27	400	108	1566	4,600	3,10