

Design and dimensions shown may be changed without prior notice

// 6D2AA

**Frac delivery 27 bar (400 psi) - Supertuff****Tube:** black synthetic elastomer.**Reinforcement:** high tensile textile cords.**Cover:** black synthetic elastomer - supertuff cover - abrasion, oil and ozone resistant.**Application:** fracking fluids, liquid mud and crude oil delivery in heavy duty oilfield and gas exploration service. Special "supertuff" cover for excellent abrasion resistance.**Temperature:** -30°C +80°C (-22°F +176°F)

ID (mm)	ID (in)	OD (mm)	OD (in)	WP (bar)	WP (psi)	BP (bar)	BP (psi)	Weight (kg/m)	Weight (lb/ft)
102,0	4"	120,0	4,72	27	400	108	1566	4,600	3,10

// 6F2AA

**Frac S&D 27 bar (400 psi)****Tube:** black synthetic elastomer.**Reinforcement:** high tensile textile cords with embedded steel helix wire.**Cover:** black synthetic elastomer - abrasion, oil and ozone resistant.**Application:** fracking fluids, liquid mud and crude oil suction and delivery in heavy duty oil field and gas exploration service.**Temperature:** -30°C +80°C (-22°F +176°F)

ID (mm)	ID (in)	OD (mm)	OD (in)	WP (bar)	WP (psi)	BP (bar)	BP (psi)	BR (mm)	BR (in)	Vacuum %	Weight (kg/m)	Weight (lb/ft)
102,0	4"	126,0	4,96	27	400	108	1566	304	11,97	90,00	6,080	4,09