

## // SEISMIC

### // 250AK



#### Seismic 5 bar (75 psi)

**Tube:** black EPDM.

**Reinforcement:** high tensile textile cords.

**Cover:** yellow EPDM with silver stripes - abrasion and ozone resistant.

**Application:** flotation buoy in seismic monitoring operations.

**Temperature:** -30 °C +80 °C (-22 °F +176 °F)

ID (mm)	ID (in)	OD (mm)	OD (in)	WP (bar)	WP (psi)	BP (bar)	BP (psi)	Weight (kg/m)	Weight (lb/ft)	Brand
305,0	12"	317,0	12,48	5	75	15	225	8,750	5,89	DH
457,0	18"	477,0	18,78	5	75	15	225	18,360	12,34	DH

### // 25SAH



#### Seismic Extra 10 bar (150psi)

**Tube:** black EPDM.

**Reinforcement:** high tensile textile cords.

**Cover:** red EPDM - abrasion and sea-water resistant.

**Application:** cable protection in seismic operations.

**Temperature:** -30 °C +80 °C (-22 °F +176 °F)

ID (mm)	ID (in)	OD (mm)	OD (in)	WP (bar)	WP (psi)	BP (bar)	BP (psi)	Weight (kg/m)	Weight (lb/ft)
102,0	4"	136,0	5,35	10	150	30	450	6,940	4,67
127,0	5"	161,0	6,34	10	150	30	450	8,630	5,80
152,0	6"	188,0	7,40	10	150	30	450	11,580	7,79