



STRAIGHT INTERMEDIATE REDUCTION

Type: 4019..



Series ORFS	40.... [bar]	41.... [bar]	Ordering Complete	Ø Tube A ^M	Ø Tube B ^M	Ø Tube A ^W	Ø Tube B ^W	Form	L1	L2	CH1	ORFS A	ORFS B
UNIVERSAL	630	630	401901	8-10	6	5/16-3/8	1/4	X	20	10	22	11/16-16	9/16-18
			401902	12	6	1/2	1/4	Y	22	10	24	13/16-16	9/16-18
	420	420	401903	14-15-16	6	5/8	1/4	Y	23	10	30	1-14	9/16-18
			401904	18-20	6	3/4	1/4	Y	25	10	36	13/16-12	9/16-18
			401905	22-25	6	7/8-1	1/4	Y	26	10	41	17/16-12	9/16-18
	280	280	401906	28-30-32	6	1 1/4	1/4	Y	26,5	10	50	11/16-12	9/16-18
			401907	35-38	6	1 1/2	1/4	Y	26,5	10	60	2-12	9/16-18
	630	630	401908	12	8-10	1/2	5/16-3/8	X	23	11	24	13/16-16	11/16-16
			401909	14-15-16	8-10	5/8	5/16-3/8	Y	24	11	30	1-14	11/16-16
	420	420	401910	18-20	8-10	3/4	5/16-3/8	Y	26	11	36	13/16-12	11/16-16
			401911	22-25	8-10	7/8-1	5/16-3/8	Y	27	11	41	17/16-12	11/16-16
			401912	28-30-32	8-10	1 1/4	5/16-3/8	Y	27,5	11	50	11/16-12	11/16-16
	280	280	401913	35-38	8-10	1 1/2	5/16-3/8	Y	27,5	11	60	2-12	11/16-16
			401914	14-15-16	12	5/8	1/2	Y	25,5	13	30	1-14	13/16-16
	420	420	401915	18-20	12	3/4	1/2	Y	27,5	13	36	13/16-12	13/16-16
			401916	22-25	12	7/8-1	1/2	Y	29	13	41	17/16-12	13/16-16
			401917	28-30-32	12	1 1/4	1/2	Y	29,5	13	50	11/16-12	13/16-16
	280	280	401918	35-38	12	1 1/2	1/2	Y	29,5	13	60	2-12	13/16-16
			401919	18-20	14-15-16	3/4	5/8	X	29,5	15,5	36	13/16-12	1-14
	420	420	401920	22-25	14-15-16	7/8-1	5/8	Y	32	15,5	41	17/16-12	1-14
			401921	28-30-32	14-15-16	1 1/4	5/8	Y	32	15,5	50	11/16-12	1-14
	280	280	401922	35-38	14-15-16	1 1/2	5/8	Y	32	15,5	60	2-12	1-14
			401923	22-25	18-20	7/8-1	3/4	X	33	17	46	17/16-12	13/16-12
	280	280	401924	28-30-32	18-20	1 1/4	3/4	Y	33,5	17	50	11/16-12	13/16-12
			401925	35-38	18-20	1 1/2	3/4	Y	33,5	17	60	2-12	13/16-12
			401926	28-30-32	22-25	1 1/4	7/8-1	X	34	17,5	50	11/16-12	17/16-12
			401927	35-38	22-25	1 1/2	7/8-1	Y	34	17,5	60	2-12	17/16-12
			401928	35-38	28-30-32	1 1/2	1 1/4	Y	34	17,5	60	2-12	11/16-12

Notes: If you wish to order a fitting in stainless steel, please change the first two digit from 40.... to 41.... .

If you wish to order AISI 316 form Y stainless steel fittings with AISI 304 stainless steel nuts, please change the first two digits from 40.... to 44.... .