

Dimensions shown may be changed without prior notice

// FLEXOR TWB1



ONE WIRE BRAID

Tube: polyester.
Reinforcement: one high tensile steel braid.
Cover: abrasion, ozone and hydrocarbon resistant polyurethane, non pin-pricked.
Application: high pressure hydraulic lines, fuel oil, antifreeze solutions, air and water.
Constant operation: -40 °C +100 °C (-40 °F +212 °F)
 air max T = +70 °C (+160 °F)
Length: random

| Item Code | ↔ | | | ↔ | | ↻ | | ↻ | | ⤴ | | ⚖ | |
|-----------|------|------|-------|-------|------|------|------|-------|-------|------|------|-------|-------|
| | Dash | mm | in | mm | in | Mpa | psi | Mpa | psi | mm | in | kg/m | lb/ft |
| 1000283 | 04 | 6,0 | 1/4" | 11,70 | 0,46 | 31,0 | 4500 | 124,0 | 18000 | 40,0 | 1,57 | 0,165 | 0,12 |
| 1000284 | 05 | 8,0 | 5/16" | 13,20 | 0,52 | 25,0 | 3630 | 100,0 | 14500 | 55,0 | 2,17 | 0,190 | 0,13 |
| 1000285 | 06 | 10,0 | 3/8" | 15,50 | 0,61 | 22,5 | 3250 | 90,0 | 13000 | 65,0 | 2,56 | 0,230 | 0,16 |
| 1000286 | 08 | 13,0 | 1/2" | 18,80 | 0,74 | 19,0 | 2750 | 76,0 | 11000 | 85,0 | 3,35 | 0,300 | 0,21 |

// FLEXOR TWB1 - TWIN



ONE WIRE BRAID

Tube: polyester.
Reinforcement: one high tensile steel braid.
Cover: abrasion, ozone and hydrocarbon resistant polyurethane, non pin-pricked.
Application: high pressure hydraulic lines, fuel oil, antifreeze solutions, air and water.
Constant operation: -40 °C +100 °C (-40 °F +212 °F)
 air max T = +70 °C (+160 °F)
Length: random

| Item Code | ↔ | | | ↔ | | ↻ | | ↻ | | ⤴ | | ⚖ | |
|-----------|------|------|-------|-------|------|------|------|-------|-------|------|------|-------|-------|
| | Dash | mm | in | mm | in | Mpa | psi | Mpa | psi | mm | in | kg/m | lb/ft |
| 1000289 | 04 | 6,0 | 1/4" | 11,70 | 0,46 | 31,0 | 4500 | 124,0 | 18000 | 40,0 | 1,57 | 0,330 | 0,23 |
| 1000288 | 05 | 8,0 | 5/16" | 13,20 | 0,52 | 25,0 | 3630 | 100,0 | 14500 | 55,0 | 2,17 | 0,380 | 0,26 |
| 1000287 | 06 | 10,0 | 3/8" | 15,50 | 0,61 | 22,5 | 3250 | 90,0 | 13000 | 65,0 | 2,56 | 0,460 | 0,31 |