

// RIGMASTER HD BULK MATERIAL DELIVERY

**Bulk material delivery - 20 bar (300 psi) - Lay Flat****Tube:** black conductive NR.**Reinforcement:** high tensile textile cords.**Cover:** black conductive CR - brasion, ozone and hydrocarbon and flame resistant.**Application:** bulk material, barite and dry cement transfer from supply vessels to offshore platforms.

Special layflat construction for reeling use.

Also available in self floating version.

Temperature: -30°C +80°C (-22°F +176°F)

ID (mm)	ID (in)	OD (mm)	OD (in)	WP (bar)	WP (psi)	BP (bar)	BP (psi)	Weight (kg/m)	Weight (lb/ft)
127,0	5"	145,0	5,71	20	300	60	900	4,510	3,04

// RIGMASTER PLUS BULK MATERIAL DELIVERY

**Bulk material delivery - 27 bar (400 psi) - Lay Flat****Tube:** black conductive NR.**Reinforcement:** high tensile textile cords.**Cover:** black conductive CR - brasion, ozone and hydrocarbon and flame resistant.**Application:** bulk material, barite and dry cement transfer from supply vessels to offshore platforms.

Special layflat construction for reeling use.

Also available in self floating version.

Temperature: -30°C +80°C (-22°F +176°F)

ID (mm)	ID (in)	OD (mm)	OD (in)	WP (bar)	WP (psi)	BP (bar)	BP (psi)	Weight (kg/m)	Weight (lb/ft)
127,0	5"	146,0	5,75	27	400	81	1200	5,340	3,59

// RIGMASTER BULK MATERIAL S&D

**Bulk material S&D 10 bar (150 psi)****Tube:** black conductive NR - abrasion resistant.**Reinforcement:** high tensile textile cords with embedded steel helix wire.**Cover:** black conductive SBR/NR - abrasion and ozone resistant.**Application:** bulk material, barite and dry cement transfer from supply vessels to offshore platforms.

Also available in self floating version.

Temperature: -30 °C +80 °C (-22 °F +176 °F)

ID (mm)	ID (in)	OD (mm)	OD (in)	WP (bar)	WP (psi)	BP (bar)	BP (psi)	BR (mm)	BR (in)	Vacuum %	Weight (kg/m)	Weight (lb/ft)
102,0	4"	116,0	4,57	10	150	30	450	306	12,05	90,00	3,030	2,04
127,0	5"	143,0	5,63	10	150	30	450	508	20,00	80,00	5,010	3,37