

Design and dimensions shown may be changed without prior notice

// RIGMASTER HD BULK MATERIAL
S&D**Bulk material S&D 20 bar (300 psi)****Tube:** black conductive NR - abrasion resistant.**Reinforcement:** high tensile textile cords with embedded steel helix wire.**Cover:** black conductive SBR/NR - abrasion and ozone resistant.**Application:** bulk material, barite and dry cement transfer from supply vessels to offshore platforms.

Also available in self floating version.

Temperature: -30 °C +80 °C (-22 °F +176 °F)

ID (mm)	ID (in)	OD (mm)	OD (in)	WP (bar)	BP (psi)	BP (bar)	WP (psi)	BR (mm)	BR (in)	Vacuum %	Weight (kg/m)	Weight (lb/ft)
127,0	5"	147,0	5,79	20	900	60	300	508	20,00	80,00	6,310	4,25

// 748AA

**Rig supply soft wall - Bulk material 20 bar (300 psi)****Tube:** black conductive NR - abrasion resistant.**Reinforcement:** high tensile textile cords - antistatic wire.**Cover:** black conductive CR - abrasion, ozone, hydrocarbon and fire resistant.**Application:** bulk material, barite and dry cement transfer from supply vessels to offshore platforms.

Specially designed for reeling applications.

Tensile end load resistance:

ID 4" 6.000 kg

ID 5" 10.000 kg.

Electrically continuous.

Also available in self floating version.

Temperature: -30 °C +80 °C (-22 °F +176 °F)

ID (mm)	ID (in)	OD (mm)	OD (in)	WP (bar)	WP (psi)	BP (bar)	BP (psi)	BR (mm)	BR (in)	Weight (kg/m)	Weight (lb/ft)
102,0	4"	122,0	4,80	20	300	80	1200	612	24,09	4,480	3,02
127,0	5"	149,0	5,87	20	300	80	1200	762	30,00	6,460	4,35

ABS Type approved hose assemblies.