

Design and dimensions shown may be changed without prior notice

// RIGMASTER HD POTABLE WATER DELIVERY**Potable water delivery 20 bar (300 psi) - Lay Flat****Tube:** white NR.**Reinforcement:** high tensile textile cords.**Cover:** orange NBR/PVC - abrasion, ozone and hydrocarbon resistant.**Application:** potable water transfer from supply vessels to offshore platforms.

Sterilize with 5% soda solution.

Specially lay flat construction for reeling use.

Also available in self floating version.

Temperature: -30 °C +80 °C (-22 °F +176 °F)

ID (mm)	ID (in)	OD (mm)	OD (in)	WP (bar)	WP (psi)	BP (bar)	BP (psi)	Weight (kg/m)	Weight (lb/ft)
102,0	4"	116,0	4,57	20	300	60	900	3,030	2,04

// RIGMASTER PLUS POTABLE WATER DELIVERY**Potable Water Delivery 27 bar (400 psi) - Lay flat****Tube:** white NR.**Reinforcement:** high tensile textile cords.**Cover:** orange NBR/PVC - abrasion, ozone and hydrocarbon resistant.**Application:** potable water transfer from supply vessels to offshore platforms.

Sterilize with 5% soda solution.

Specially lay flat construction for reeling use.

Also available in self floating version.

Temperature: -30 °C +80 °C (-22 °F +176 °F)

ID (mm)	ID (in)	OD (mm)	OD (in)	WP (bar)	WP (psi)	BP (bar)	BP (psi)	BR (mm)	BR (in)	Weight (kg/m)	Weight (lb/ft)
102,0	4"	117,0	4,61	27	400	81	1200	510	20,08	3,100	2,09