

SEMPERJET 2 SN

High pressure hose for pressure washer applications,
exceeds EN1829-2 and ISO 7751 class 6



Dimensions and tolerances acc. to DIN EN 853 2SN

For cold and hot water up to 155°C [310°F]

GENERAL

Tube	Synthetic rubber, resistant against cold and hot water with usual cleaning agents
Reinforcement	Two braids of high tensile steel wire
Cover	Abrasion and ozone resistant synthetic rubber Standard cover: Black, blue or grey [Available on request with black, blue and grey cover acc. to committee for Product Safety AfPS GS 2019:01 / Category 2 b.]
Temperature range	-10°C to 155°C / 14°F to +310°F
Standard branding	Embossed tape
Note	Not suitable for steam and oil hydraulic applications

TECHNICAL DETAILS

																
Nominal			Internal-Ø		Braid-Ø		External-Ø		Work. pressure [max.]		Min. burst pressure		Bending radius [min.]		Weight approx.	
mm	inch	dash	mm	inch	mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	lbs/ft	kg/m
6	1/4	-4	6.6	0.26	12.4	0.49	14.3	0.56	400	5800	1600	23205	100	3.9	0.21	0.31
8	5/16	-5	8.3	0.33	14.0	0.55	16.0	0.63	400	5800	1400	20305	115	4.5	0.25	0.37
10	3/8	-6	9.9	0.39	16.4	0.65	18.4	0.72	400	5800	1320	19145	125	4.9	0.30	0.44
12	1/2	-8	13.0	0.51	19.4	0.76	21.3	0.84	400	5800	1100	15955	180	7.1	0.38	0.56