

ECO 6000

High pressure hose for pressure washer applications,
exceeds ISO 7751 class 6



For cold and hot water up to 155°C [310°F]

GENERAL

Tube	Synthetic rubber, resistant against cold and hot water with usual cleaning agents
Reinforcement	Two braids of high tensile steel wire
Cover	Abrasion and ozone resistant synthetic rubber Standard cover: Black, blue or grey
Temperature range	-10°C to 155°C / 14°F to +310°F
Standard branding	Embossed tape
Note	Not suitable for steam and oil hydraulic applications

TECHNICAL DETAILS

																
Nominal			Internal-Ø		Braid-Ø		External-Ø		Work. pressure [max.]		Min. burst pressure		Bending radius [min.]		Weight approx.	
mm	inch	dash	mm	inch	mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	lbs/ft	kg/m
6	1/4	-4	6.6	0.26	11.7	0.46	13.6	0.54	414	6000	1242	18015	75	3.0	0.20	0.3
8	5/16	-5	8.3	0.32	13.1	0.51	15.3	0.60	414	6000	1242	18015	85	3.3	0.23	0.34
10*	3/8	-6	9.9	0.39	14.5	0.57	16.3	0.64	420	6090	1260	18275	65	2.6	0.22	0.33
12	1/2	-8	13.0	0.51	18.8	0.74	21.0	0.83	414	6000	1242	18015	130	5.1	0.40	0.59

*s-version