

PL1

Air/Water - 20 bar - yellow



SPECIFICATIONS

Application	Suitable for delivering compressed air and water in power plant, road construction, tunneling and quarrying.
Feature	Easily identified due to distinctive colour.
Temperature range	-40°C / +100°C.
Safety factor	3 : 1
Tube	EPDM, black, suitable for oil-laden air, smooth.
Reinforcement	Textile spiral [DN > 25 wrapped].
Cover	EPDM, yellow, resistant to ozone and weather, abrasion resistant, smooth [DN > 25 cloth impression].
Marking	continuous inkjet, black letters: DN >25 continuous mylartape, blue letters: "SEMPERIT (S) PL1 Druckluft/Wasser Air/Water Mammut WP 20 bar/BP 60 bar MADE IN EU // // // // //".

TECHNICAL DETAILS

Article number	Internal-Ø		Wall width	External-Ø	Work. pressure [max.]	Number of inserts	Bending radius [min.]	Weight approx.	Coil length [max.]
	mm	inch							
68416 1350	13,0	1/2	5,0	23,0	20	2	80	0,43	50
68416 1950	19,0	3/4	5,0	29,0	20	2	150	0,52	50
68416 1955	19,0	3/4	5,5	30,0	20	2	150	0,59	50
68416 1960	19,0	3/4	6,0	31,0	20	2	150	0,65	50
68416 2560	25,0	1	6,0	37,0	20	2	185	0,82	50
68416 2570	25,0	1	7,0	39,0	20	2	185	0,95	50
48426 3260	32,0	1 1/4	6,0	44,0	20	2	260	1,00	40
48426 3860	38,0	1 1/2	6,0	50,0	20	2	350	1,16	40
48426 5080	50,0		8,0	66,0	20	4	400	2,30	40
48426 5010	50,0		10,0	70,0	20	4	330	3,00	40
48426 5380	53,0		8,0	69,0	20	4	420	2,45	40
48426 5310	53,0		10,0	73,0	20	4	350	3,10	40
48426 6310	63,5	2 1/2	10,0	83,5	20	4	480	2,90	40
48426 7510	75,0	3	10,0	95,0	20	4	610	3,50	40
56426 1014	101,6	4	14,0	129,6	20	8	720	6,60	40