

TU20

Mineral oil - 20 bar



SPECIFICATIONS

Application	The TU20 hose quality is known as a very well established multipurpose hose which can be used in various applications as for example in industry, construction, agriculture or vehicle repair shops
Feature	Our TU20 product can be used for E5 (EN 228:2017) and E10 as well for B7 (EN 590:2017) and B20 with a maximum aromatic content of 50%. For the usage with B100 (pure biodiesel / 100% FAME/RME) as well as E85 and E100 a sufficient suitability needs to be checked under real working conditions prior usage.
Standard/Approval	BS 2050:1978. BS ISO 2878:2017.
Temperature range	-40°C / +100°C.
Safety factor	3 : 1
Tube	NBR, black, electrically conductive, smooth.
Reinforcement	Textile spiral.
Cover	NBR/EPDM, black, resistant to ozone and weather, abrasion resistant, resistant to oil, electrically conductive, smooth.
Marking	continuous inkjet, white letters: "SEMPERIT (S) TU 20 NBR Öl/Luft Oil/Air PN 20 bar Conductive R < 10 ⁶ Ohm/m".
Notice	The usage of our product is only allowed for land and sea applications. ATTENTION: For last valid information regarding oil & fuel suitability please always refer to the Semperit oil & fuel suitability matrix or, in case of doubt, contact Semperit. ATTENTION: Not to be used as a petrol pump hose. ATTENTION: Not suitable for the usage as fuel line hose of vehicles and in engine compartments. ATTENTION: Not suitable for supply of any engine-driven vehicles