

FBD

Air Brake - 10 bar - DIN 74310



SPECIFICATIONS

Application	Brake hose for vehicle air brake systems and other pneumatic systems in vehicles and trailers.
Standard/Approval	DIN 74310:1993.
Temperature range	-40°C / +70°C.
Safety factor	5 : 1 [exceeds DIN 74310:1993]
Tube	EPDM, black, smooth.
Reinforcement	Textile spiral.
Cover	EPDM, black, resistant to ozone and weather, abrasion resistant, smooth.
Marking	continuous inkjet, white letters: "SEMPERIT (S) FBD Bremsschlauch/Air-Brake DIN 74310 - ID - PN 10 bar WW YY MADE IN EU //////////////".
Notice	100% pressure tested. Complete inside diameter checked using a ball test.

TECHNICAL DETAILS

Article number	Internal-Ø		Wall width		External-Ø		Work. pressure [max.]	Number of inserts	Bending radius [min.]	Weight approx.	Coil length [max.]
	mm	inch	mm	mm	mm	bar					
68430 0935	9.0		3.5	16.0	10	2	65	0.20	50		
68430 1135	11.0	7/16	3.5	18.0	10	2	70	0.22	50		
68430 1360	13.0	1/2	6.0	25.0	10	2	80	0.48	50		