

FKD-R

Cooling - EPDM - 6 bar



SPECIFICATIONS

Application	Cooling hose for combustion engines.
Feature	Good resistance to ageing under the influence of hot water, hot air and anti-freezing agents. Ozone resistant.
Temperature range	-40°C / +120°C.
Safety factor	2,5 : 1
Tube	EPDM, black, smooth.
Reinforcement	Textile spiral.
Cover	EPDM, black, resistant to ozone and weather, smooth.
Marking	continuous inkjet, white letters: "SEMPERIT (S) FKD Kühlwasser/Cooling Water ID x WT >EPDM/PES/EPDM< XQ/YYYY -40°C / +120°C MADE IN EU // // // //".
Notice	ATTENTION: As temperature increases or decreases, burst pressure, safe working pressure, coupling retention properties and other safety characteristics of the hose can significantly decrease in closed systems/applications. Failure to consider how temperature and other conditions affect hose performance may cause property damage, serious bodily injury or death.

TECHNICAL DETAILS

Article number	Internal-Ø		Wall width	External-Ø	Work. pressure [max.]	Number of inserts	Bending radius [min.]	Weight approx.	Coil length [max.]
	mm	inch							
68201 1035	10.0	3/8	3.5	17.0	6	2	60	0.22	50
68201 1235	12.0		3.5	19.0	6	2	70	0.25	50
68201 1236	12.5	1/2	3.5	19.5	6	2	75	0.26	50
68201 1335	13.0		3.5	20.0	6	2	80	0.27	50
68201 1435	14.0	9/16	3.5	21.0	6	2	85	0.28	50
68201 1535	15.0		3.5	22.0	6	2	90	0.31	50
68201 1540	15.0		4.0	23.0	6	2	90	0.36	50
68201 1635	16.0	5/8	3.5	23.0	6	2	95	0.32	50
68201 1835	18.0		3.5	25.0	6	2	110	0.34	50
68201 1935	19.0	3/4	3.5	26.0	6	2	115	0.35	50
68201 2035	20.0		3.5	27.0	6	2	120	0.38	50
68201 2235	22.0	7/8	3.5	29.0	6	2	135	0.39	50
68201 2535	25.0	1	3.5	32.0	6	2	150	0.46	50
68201 3255	32.0	1 1/4	5.5	43.0	6	2	195	0.96	50