

LM1-EPDM

Food - EPDM - 12 bar - D - red



SPECIFICATIONS

Application	LM1 EPDM the flexible discharge hose for use in breweries and the food and beverage industries. Suitable for use with alcohol (max. 40%) and soft drinks, fatty (max. 36%) and non-fatty foods.
Feature	We don't use for the tube compound of LM1 EPDM any PHTHALATES PAH we comply with requirements of EU 1907/2006 (REACH), Annex XVII Nr. 50
Standard/Approval	BfR XXI Kat. 2, FDA [CFR 21 § 177.2600], EG1935/2004. REACH regulation and REACH consumer goods annex XVII
Temperature range	-35°C / +95°C, steam cleaning without pressure up to 130°C / max. 30 min.
Safety factor	3,15 : 1
Tube	EPDM, white, food quality, smooth.
Reinforcement	Textile wrapped.
Cover	EPDM, red, resistant to ozone and weather, abrasion resistant, cloth impression.
Marking	continuous mylartape, white letters: "SEMPERIT [S] LM1-EPDM Lebensmittel BfR XXI Kat.2 BREWER/KELLERMEISTER D food quality FDA WP 12 BAR Made in EU".
Notice	Very high resistance to many aggressive cleaning agents. For the application of cleaning agents please see our separate information sheet. ATTENTION: Not suitable for dry conveyance.